

⇒ Powder-free ambidextrous short length (240 mm / 9.4") non-sterile nitrile gloves.

SIZES	6/XS	7/S	8/ <b>M</b>	9/L	10/XL
CODES	87 2121	87 2122	87 2123	87 2124	87 2125

DESCRIPTION	
FORMULATION	Nitrile synthetic rubber (acrylonitrile butadiene).
DESIGN	Black, ambidextrous, beaded cuff, finger textured.
PACKAGING	100 gloves per dispenser - 10 dispensers per case.

NOMINAL	L THICKNESS	mm	mil	Norm
⇒ Fing	ger	0.19	7.5	ASTM D3767-03 (2014)
⇒ Palı	m	0.12	4.7	
⇒ Cuf	ff	0.10	3.9	

LENGTH	Minimum	Typical	Norm
⇒ From middle finger tip to edge of cuff	≥ 240 mm / 9.4"	245 mm / 9.6"	EN 420:2003+A1:2009

	ENGTH PERTIES	Force a		Ultimate elongation	Force at break	Norm
$\Rightarrow$	Before aging	≥ 6.0N	14 Mpa	≥ 500%	8.0N	EN 455-2:2015
$\Rightarrow$	After aging	≥ 6.0N	14 Mpa	≥ 400%	7.0N	ASTM D573-04 (2015)

FREEDOM FROM HOLES	Performance	Norm
⇒ Acceptable Quality Level (AQL)	< 1.5 <sup>1</sup> - Level 2	EN 455-1:2000

<sup>&</sup>lt;sup>1</sup>AQL as defined per ISO 2859-1:1999 for sampling by attributes.



Dr. Willem Dreeslaan 1 ° 6721 ND Bennekom ° The Netherlands Phone +31 (0)317 700 202 ° Fax +31 (0)318 503 742 E-mail: <u>Info@shieldscientific.com</u> www.shieldscientific.com